



SYSTIMAX 360™ iPatch® Evolve High Density F/UTP Modular Panel, 48 port

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	SYSTIMAX®
Product Type	RJ45 patch panel
Product Brand	SYSTIMAX 360™ iPatch®

General Specifications

ANSI/TIA Category	6A
Cable Type	Shielded
Color	Silver
Intelligence Type	iPatch® enabled
Panel Style	Straight
Rack Units	2
Total Ports, quantity	48
Wiring	T568A T568B

Dimensions

Height	89.66 mm 3.53 in
Width	482.6 mm 19 in
Depth	206.5 mm 8.13 in
Compatible Diameter Over Dielectric, maximum	1.168 mm 0.046 in

Electrical Specifications

Current Rating at Temperature	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS, conductive surface	1,500 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm

Mechanical Specifications

Plug Insertion Life, minimum

750 times

Environmental Specifications

Operating Temperature

-10 °C to +60 °C (+14 °F to +140 °F)

Storage Temperature

-40 °C to +70 °C (-40 °F to +158 °F)

Safety Standard

UL | cUL

Packaging and Weights

Packaging quantity

1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

